

Ferrous Standard Saw Blades

FERROUS AND STAINLESS STEEL

HSS/DMo5 (M2) Fully Hardened and Tempered to 63/65Rc. Black Finish (BL-OV) Steam Oxide Vapor Treatment Standard.

Part Number	Diameter		Kerf mm	Bore Size	Pinholes Qty./Dia./B.C.	Hub Diameter
	mm	in.				
CF600A	160mm	6.30"	1.2mm	32mm	1/8/50 1/9/60	99mm
CF602A	160mm	6.30"	1.5mm	32mm	1/8/50 1/9/60	99mm
CF604A	200mm	7.87"	2.0mm	32mm	2/8.5/45 2/12/64	90mm
CF606A	200mm	7.87"	2.0mm	32mm	2/8.5/45 4/9/50 2/12/64	90mm
CF608A	225mm	8.86"	1.6mm	32mm	2/8.5/45 4/9/50 2/12/64	90mm
CF610A	225mm	8.86"	1.6mm	40mm	2/9/55 4/12/64	140mm
CF612A	225mm	8.86"	2.0mm	32mm	2/8.5/45 4/9/50 2/12/64	90mm
CF614A	225mm	8.86"	2.0mm	32mm	2/8.5/45 2/12/64	90mm
CF616A	225mm	8.86"	2.0mm	40mm	2/9/55 4/12/64	140mm
CF618A	250mm	9.84"	1.6mm	40mm	2/9/55 4/12/64	90mm
CF620A	250mm	9.84"	1.6mm	32mm	2/8.5/45 2/12/64	90mm
CF622A	250mm	9.84"	2.0mm	32mm	2/8.5/45 2/12/64	90mm
CF624A	250mm	9.84"	2.0mm	32mm	2/8.5/45 4/9/50 2/12/64	110mm
CF626A	250mm	9.84"	2.0mm	40mm	2/9/55 4/12/64	90mm
CF628A	250mm	9.84"	2.5mm	32mm	2/8.5/45 2/12/64	90mm
CF630A	250mm	9.84"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	110mm
CF632A	250mm	9.84"	2.5mm	40mm	2/9/55 4/12/64	90mm
CF634A	275mm	10.83"	2.0mm	32mm	2/8.5/45 2/12/64	100mm
CF636A	275mm	10.83"	2.0mm	40mm	2/9/55 4/12/64	100mm
CF638A	275mm	10.83"	2.5mm	32mm	2/8.5/45 2/12/64	100mm
CF640A	275mm	10.83"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	110mm
CF642A	275mm	10.83"	2.5mm	40mm	2/9/55 4/12/64	100mm
CF644A	275mm	10.83"	3.0mm	32mm	2/8.5/45 2/12/64	100mm
CF646A	275mm	10.83"	3.0mm	40mm	2/9/55 4/12/64	100mm
CF648A	300mm	11.81"	2.5mm	32mm	2/8.5/45 2/12/64	100mm
CF650A	300mm	11.81"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	110mm
CF652A	300mm	11.81"	2.5mm	38mm	2/9/55	100mm
CF654A	300mm	11.81"	2.5mm	40mm	2/9/55 4/12/64	100mm
CF656A	300mm	11.81"	3.0mm	32mm	2/8.5/45 4/9/50 2/12/64	100mm
CF658A	300mm	11.81"	3.0mm	40mm	2/9/55 4/12/64	100mm
CF660A	300mm	11.81"	3.5mm	32mm	2/8.5/45 2/12/64	100mm
CF662A	300mm	11.81"	3.5mm	40mm	2/9/55 4/12/64	100mm

A = Available Item Shipped within 8 working days from the time the order is placed.

Bore sizes and mounting holes not listed are available by special quote only.

The number of teeth in Ferrous and Stainless Cutting Cold Saws are to be taken from the chart on page 44 & 45.

Ferrous Standard Saw Blades

FERROUS AND STAINLESS STEEL

HSS/DMo5 (M2) Fully Hardened and Tempered to 63/65Rc. Black Finish (BL-OV) Steam Oxide Vapor Treatment Standard.

Part Number	Diameter		Kerf mm	Bore Size	Pinholes Qty./Dia./B.C.	Hub Diameter
	mm	in.				
CF664A	315mm	12.40"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	100mm
CF666A	315mm	12.40"	2.5mm	32mm	2/8.5/45 2/12/64	100mm
CF668A	315mm	12.40"	2.5mm	40mm	2/9/55 4/12/64	100mm
CF670A	315mm	12.40"	3.0mm	32mm	2/8.5/45 4/9/50 2/12/64	100mm
CF672A	315mm	12.40"	3.0mm	32mm	2/8.5/45 2/12/64	100mm
CF674A	315mm	12.40"	3.0mm	40mm	2/9/55 4/12/64	100mm
CF676A	325mm	12.80"	2.5mm	32mm	2/8.5/45 2/12/64	100mm
CF678A	325mm	12.80"	2.5mm	40mm	2/9/55 4/12/64	100mm
CF680A	325mm	12.80"	3.0mm	40mm	2/9/55 4/12/64	100mm
CF682A	350mm	13.78"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	120mm
CF684A	350mm	13.78"	2.5mm	32mm	2/8.5/45 2/12/64	120mm
CF686A	350mm	13.78"	2.5mm	40mm	2/9/55 4/12/64	120mm
CF688A	350mm	13.78"	2.5mm	50mm	4/15/80 4/15/85	120mm
CF690A	350mm	13.78"	3.0mm	32mm	2/8.5/45 2/12/64	120mm
CF692A	350mm	13.78"	3.0mm	32mm	2/8.5/45 4/9/50 2/12/64	120mm
CF694A	350mm	13.78"	3.0mm	40mm	2/9/55 4/12/64	120mm
CF696A	350mm	13.78"	3.0mm	50mm	2/9/55 4/12/64	120mm
CF698A	370mm	14.57"	3.0mm	32mm	2/8.5/45 2/12/64	120mm
CF700A	370mm	14.57"	3.0mm	40mm	2/9/55 4/12/64	120mm
CF702A	370mm	14.57"	3.0mm	50mm	4/15/80 4/15/85	120mm
CF704A	400mm	15.75"	3.0mm	40mm	2/9/55 4/12/64	120mm
CF706A	400mm	15.75"	3.0mm	50mm	4/15/80 4/15/85	120mm
CF708A	400mm	15.75"	3.5mm	40mm	2/9/55 4/12/64	120mm
CF710A	400mm	15.75"	3.5mm	50mm	4/15/80 4/15/85	120mm
CF712A	425mm	16.73"	3.5mm	40mm	2/9/55 4/12/64	120mm
CF714A	425mm	16.73"	3.5mm	50mm	4/15/80 4/15/85	120mm
CF716A	450mm	17.72"	3.5mm	40mm	2/9/55 4/12/64	130mm
CF718A	450mm	17.72"	4.0mm	40mm	2/9/55 4/12/64	130mm
CF720A	450mm	17.72"	3.5mm	50mm	4/15/80 4/15/85	130mm

A = Available Item Shipped within 8 working days from the time the order is placed.

Bore sizes and mounting holes not listed are available by special quote only.

The number of teeth in Ferrous and Stainless Cutting Cold Saws are to be taken from the chart on page 44 & 45.