



E-Series Main Panel Saw Blades

(For Cutting: MDG, Laminated & Raw MDF, Plywood, Particle Board)



Features

- Used for cutting single and stacked sheets of laminated or raw MDF, Particleboard, Plywood, etc.



Part No.	Diameter	Teeth	Bore Size	Hook Angle	Kerf	Plate	Keyways or Holes Qty.-Dia.-B.C.
SC720	220	64	30	-5°	2.9	2.1	2/7/42
SC724	300	60	30	10°	4.4	3.2	
SC724-01	300	60	80	10°	4.4	3.2	4-9-100
SC724-02	300	60	80	10°	4.4	3.2	2-14-110
SC724-03	300	60	50	10°	4.4	3.2	3/15/80
SC724-04	300	60	75	10°	4.4	3.2	
SC724-05	300	60	65	10°	4.4	3.2	2-9-110
SC725	300	72	75	10°	4.4	3.2	
SC719	300	96	30	-5°	3.2	2.4	2/10/60
SC733	350	60	75	12°	4.4	3.2	
SC731	350	72	30	10°	4.4	3.2	
SC731-01	350	72	80	10°	4.4	3.2	
SC731-02	350	72	80	10°	4.4	3.2	2-14-110
SC731-03	350	72	75	10°	4.4	3.2	
SC731-04	350	72	80	10°	4.4	3.2	2-7-110
SC731-05	350	72	30	10°	4.4	3.2	4-9-100
SC731-06	350	72	80	10°	4.4	3.2	4-15-110
SC731-07	350	72	80	10°	4.4	3.2	2-9-130
SC731-08	350	72	80	10°	4.4	3.2	4-8-100
SC731-09	350	72	80	10°	4.4	3.2	2-14-100
SC731-10	350	72	80	10°	4.4	3.2	2-7-110
SC738	370	72	30	10°	4.4	3.2	
SC741	380	72	60	10°	4.8	3.5	2-14-100
SC741-01	380	72	75	10°	4.8	3.5	2-14-100 + 3-15-75
SC741-02	380	72	75	10°	4.8	3.5	2-14-100

SC745Q	400	72	30	10°	4.4	3.2	
SC745-01	400	72	60	10°	4.4	3.2	1/11/08
SC746Q	400	72	75	10°	4.4	3.2	4-15-105
SC746-01	400	72	80	10°	4.4	3.2	4-15-105 + 2-14-110
SC746-02	400	72	80	10°	4.4	3.2	4-15-105 + 4-9-100
SC746-03	400	72	80	10°	4.4	3.2	4-15-105 + 2-7-110
SC746-04	400	72	80	10°	4.4	3.2	4-15-105 + 4-19-120
SC746-05	400	72	80	10°	4.4	3.2	4-15-105 + 2-9-130
SC751	420	72	60	10°	4.8	3.2	
SC757	430	72	80	15°	4.4	3.2	4-19-120 + 2-8.4-130
SC761	450	72	30	12°	4.4	3.2	
SC761-01	450	72	80	12°	4.4	3.2	4-9-100
SC761-02	450	72	80	12°	4.4	3.2	2-14-110
SC761-03	450	72	80	12°	4.4	3.2	2-7-110
SC761-04	450	72	80	12°	4.4	3.2	
SC761-05	450	72	75	12°	4.4	3.2	
SC762Q	450	72	60	12°	4.8	3.5	2-14-125
SC762-01	450	72	80	12°	4.8	3.5	2-14-125 + 4-19-120
SC762-02	450	72	80	12°	4.8	3.5	2-14-125 + 2-9-130
SC762-03	450	72	80	12°	4.8	3.5	2-14-125
SC771	470	72	75	15°	4.8	3.5	4-15-105
SC774	480	72	80	15°	4.8	3.5	4-19-120 + 2-8.4-130
SC775	480	72	30	15°	4.4	3.2	
SC781	500	72	60	15°	4.8	3.5	2-10-80 + 2-11-115
SC781-01	500	72	80	15°	4.8	3.5	2-10-80 + 2-11-115 + 4-9-100
SC781-02	500	72	80	15°	4.8	3.5	2-10-80 + 2-11-115 + 2-14-110
SC781-03	500	72	80	15°	4.8	3.5	2-10-80 + 2-11-115 + 2-7-110
SC782	500	60	60	15°	4.8	3.5	2-11-115
SC792	600	72	60	15°	5.8	4	2-11-115 + 2-19-120