


High-Performance Scoring Blades

(For Cutting: MDG, Laminated & Raw MDF, Plywood, Particle Board)




Features

- Designed specifically for high-powered panel saws machines and sliding table saws
- Exceptional tool life and cut quality for reduced cost-per-cut
- Resharpenable at your regional MaxxLife service center

Adjusting Scoring

The width and depth of the score (B1) is obtained by adjusting the height of the scoring blade into the material. Increasing blade height increases score width and depth.



Part No.	Diameter	Teeth	Bore Size	Hook Angle	Kerf	Plate	Keyways or Holes Qty.-Dia.-B.C.	Machine
455-9A00	80	12	20	0°	3.1-4.3	2.2		
455-9A01	100	20	20	0°	3.1-4.3	2.2		Schelling
455-9A02	105	16	45	0°	3.1-4.3	2.2		Kraftlyne
455-9A03	120	24	20	0°	3.1-4.3	2.2		
455-9A04	120	24	22	0°	3.1-4.3	2.2		
455-9A05	120	24	30	0°	3.1-4.3	2.2		
455-9A06	125	24	20	0°	3.1-4.3	2.2		Panhans
455-9A07	125	24	20	0°	3.1-4.3	2.2	2/8/42	Frama
455-9A08	125	24	22	0°	3.1-4.3	2.2		Panhans
455-9A09	125	24	45	0°	4.4-5.6	3.2		Giben-Homag
455-9A10	125	24	20	0°	4.4-5.6	3.2		Gabbiani-SCM
450-9A00	150	24	20	8°	4.4-5.6	3.2		Schelling
450-9A01	150	24	30	8°	4.4-5.6	3.2		SCM
450-9A02	150	24	45	8°	4.4-5.6	3.2		Homag
450-9A03	160	36	45	8°	4.4-5.6	3.2	3/13/80	
450-9A04	160	36	55	8°	4.4-5.6	3.2	3/7/66	Gabbiani-SCM
450-9A05	180	28	30	8°	4.4-5.6	3	2/7/42 + 2/10/60	Panhans
450-9A06	180	36	45	8°	4.8-5.8	3.5		Holzma
450-9A07	180	42	50	8°	4.4-5.6	3.2	3/13/80	Giben
450-9A08	180	36	45	8°	4.4-5.6	3.2	3/13/80	Giben
450-9A09	180	36	45	8°	4.4-5.6	3.2		Holzma
450-9A10	200	36	20	8°	4.4-5.6	3.2	2/9/110 + 2/11/66	Schelling
450-9A11	200	36	30	8°	4.4-5.6	3.2	2/9/60	Scheer

450-9A12	200	36	45	8°	4.8-5.8	3.5		Holzma
450-9A13	200	36	65	8°	4.8-5.8	3.5	2/9/100 + 2/9/110	Selco
450-9A14	200	42	50	8°	4.4-5.6	3.2	3/13/80	Giben Smart 65
450-9A15	200	36	20	8°	5.5-6.7	3.4		Schelling
450-9A16	200	36	45	8°	5.5-6.7	3.4		Holzma
450-9A17	200	36	65	8°	4.4-5.6	3.2	2/9/100 + 2/9/110	Selco
450-9A18	200	36	80	8°	4.4-5.6	3.2	2/14/110	Gabbiani
450-9A19	200	36	45	8°	5.8-6.8	3.5		Holzma
450-9A20	200	36	45	8°	6.2-7.2	4		Holzma
450-9A21	215	42	50	8°	4.4-5.6	3.2	3/15/80	Giben
450-9A22	215	42	50	8°	4.8-5.8	3.5	3/15/80	Giben
450-9A23	220	36	20	8°	6.5-7.4	4.5		Schelling
450-9A24	250	42	50	8°	4.4-5.6	3.2	3/13/80	Giben 2
450-9A25	300	48	50	8°	4.4-5.6	3.2	3/15/80	Giben
450-9A26	300	48	65	8°	4.4-5.6	3.2	2/9/100 + 2/9/110	Selco EB